



## Select Access® Freestanding Guardrail - Folding

Generated on 11.07.2020

### Detailed description

Freestanding folding guardrail system protecting against fall from height. It is the best solution to secure terraces when it is technically not possible to fix the guardrail to either a parapet wall or concrete slab.

The system overcomes the problem of having to drill the roof membrane and has been designed for a quick and simple installation, notably thanks to the swage handrails and middle rails.

The plastic 12.5 kg counterweights and clipped pads ensure a complete protection of the waterproofing. The guardrail can be also used to secure skylights or to demark working or evacuation areas. Compliant with BS EN ISO 14122-3.

### Product guidance - As Standard

#### Height:

1000–1100 mm.

#### Length:

Available in 3 m lengths.

#### Material:

Aluminium.

#### Middle rail spacing (maximum):

500 mm.

#### Upright/ counterweight spacing (maximum):

1500 mm (750 mm from an edge/ corner).

### Product specification

#### Manufacturer

- Name: Select Access Premier Solutions
- Web: [www.selectaccess.ie](http://www.selectaccess.ie)
- Email: [info@selectaccess.ie](mailto:info@selectaccess.ie)
- Tel: +353 (0)1 4642534
- Address: Unit A22, Kingswood Business Park, Baldonnell, Dublin 22

Select Access Premier Solutions



#### Select Access Premier Solutions

Unit A22  
Kingswood Business Park  
Baldonnell  
Dublin 22

Tel: +353 (0)1 4642534

[www.selectaccess.ie](http://www.selectaccess.ie)  
[info@selectaccess.ie](mailto:info@selectaccess.ie)



<b>Product reference</b>	VAP-R2 VAP-R3 - Includes toeboard, 20 x 100 mm.
<b>Arrangement</b>	As drawing - Insert drawing reference.
<b>Finish/ Colour</b>	Anodized Mill Powder coated - Insert RAL colour requirement.
<b>Safety gate</b>	Not required Required - 500 mm high.