



Restraint Straps

Generated on 20.01.2020

Detailed description

Restraint Straps are manufactured in two types: Heavy Duty to provide horizontal restraint and Standard to provide vertical restraint against wind pressure and uplift forces.

Features:

- Manufactured from pre-galvanized steel strips with zinc coated edges to BS EN 10346: 2009, DX51D + Z275 or stainless steel to BS EN 10088-1: 1995: 1.4301.
- Hole diameters are 6 mm, 12.5 mm apart, grouped in threes diagonally across the width of the strap.

Fixings:

- For Heavy Duty and Standard straps: Use either no. 12 x 50 mm wood screws or 4 x 75 mm corrosion resistant nails.
- For stainless steel straps, stainless steel fixings must be used.

Product guidance - As Standard

Dimensions (w x t):

- Heavy Duty: 27.5 x 5 mm.
- Standard: 27.5 x 2.5 mm.

Options

Length (maximum):

- Standard: 4000 mm.
- Heavy Duty: 4800 mm.
- Stainless steel: 3000 mm.

Insert overall length and distance of bend/ twist from the end of the strap, e.g. 1000 mm, bent at 100 mm = ST1000B100.

Product specification

Manufacturer

- Name: Expamet Building Products
- Web: www.expamet.co.uk
- Email: sales@expamet.net
- Tel: +44 (0)191 410 6631

Expamet Building Products



Expamet Building Products

Mary Avenue
Birtley
Co Durham
DH3 1JF

Tel: +44 (0)191 410 6631

www.expamet.co.uk
sales@expamet.net



- Fax: +44 (0)191 410 0650

- Address: Mary Avenue, Birtley, Co Durham DH3 1JF

Product reference Restraint Straps

Type
Standard (ST)
Standard, stainless steel (STSS)
Heavy Duty (HD)
Heavy Duty, stainless steel (HDSS)

Length []