



INTRAgrille XT™

Generated on 21.05.2019

Detailed description

Architectural stainless steel DDA-compliant floor grilles, suitable for heavy duty, high traffic areas.

Features:

- DDA-compliant, suitable for wheelchair access.
- Heel proof open construction - allows dirt and moisture to fall through into the matwell below.
- Optimum dirt and moisture removal.
- Suitable for a wide range of fibre inserts.

Applications:

- High traffic environments.
- Internal – choose from Elite polyamide, Premier polyamide, and polypropylene inserts.

Can be used in conjunction with wheelchairs and shopping trolleys, and the material is heel-proof.

Installation:

Can be installed into suitable recessed matwell area (surface level with adjoining floor covering), or surface mounted with the use of ramped edging.

Product guidance - As Standard

Depth:

14 mm.

Construction:

- Open construction.
- Stainless steel profile INTG42, grade 316 (1.4401).
- All inserts recyclable/ re-usable.

Options

Inserts:

- INTRAlux Elite polyamide fibre:

601 Red; 602 Blue; 604 Coco; 605 Brown; 606 Grey; 607 Anthracite; 608 Black; 609 Purple; 610 Turquoise.

- INTRAlux Linear Polypropylene:

INTRAsystems



INTRAsystems

INTRAsystems
14 Headlands Business Park
Salisbury Road, Blashford
Ringwood
Hants
BH24 3PB

Tel: +44 (0)1425 472000

www.intrasystems.co.uk
info@intrasystems.co.uk



443 Anthracite; 451 Grey.

- INTRAlux Premier polyamide:

130 Black; 138 Slate Grey.

- INTRAlux Select polyamide fibre:

50 Black; 73 Grey.

Product specification

Manufacturer

- Name: INTRAsystems
- Web: www.intrasystems.co.uk
- Email: info@intrasystems.co.uk
- Tel: +44 (0)1425 472000
- Fax: +44 (0)1425 481981
- Address: INTRAsystems, 14 Headlands Business Park, Salisbury Road, Blashford, Ringwood, Hants BH24 3PB

Product reference	INTRAgrille XT™
Plate width	21 mm (single module) - 24.3 kg/m ² . 57 mm (double module) - 23.4 kg/m ² .
Inserts	Elite polyamide fibre, colour - Insert colour requirement from 'Options' below. Polypropylene, colour - Insert colour requirement from 'Options' below. Premier polyamide, colour - Insert colour requirement from 'Options' below.
Matwell frame	Not required INT019