



INTRAlux Elite

Generated on 26.05.2020

Detailed description

High quality polyamide secondary sheet fibre, manufactured from 100% Econyl regenerated nylon yarn.

Features:

- 1080 g/m² pile weight for high durability and comfort.
- Polyamide fibre for effective moisture absorption – 5.4 L/m².
- Suitable for surface mounted or shallow recessed applications.
- High fire resistance and acoustic absorption.
- Available as an insert within aluminium system.
- Five year warranty.

Applications:

- All commercial applications.
- Zones 2 and 3.

Installation:

- With the surface of mat level with adjoining floor coverings.
- Surface mounted with low profile ramped edging trim.

Product guidance - As Standard

Material:

1080 g/m² pile weight recycled polyamide fibre with polyvinyl chloride (PVC) backing.

Construction:

Econyl recycled polyamide yarn (100%) and vinyl backing.

Roll size:

25 x 2 m.

Depth:

9.7 mm.

Weight:

4.3 kg/m².

Fire rating:

Cfl-s1.

INTRAsystems



INTRAsystems

INTRAsystems

14 Headlands Business Park
Salisbury Road, Blashford

Ringwood

Hants

BH24 3PB

Tel: +44 (0)1425 472000

www.intrasystems.co.uk
info@intrasystems.co.uk



Sustainability:

100% Econyl fibre, phthalate free backing.

Product specification

Manufacturer

- Name: INTRAsystems
- Web: www.intrasystems.co.uk
- Email: info@intrasystems.co.uk
- Tel: +44 (0)1425 472000
- Fax: +44 (0)1425 481981
- Address: INTRAsystems, 14 Headlands Business Park, Salisbury Road, Blashford, Ringwood, Hants BH24 3PB

Product reference INTRALux Elite, Polyamide Sheet Barrier Matting

Colour

- 601 Red
- 602 Blue
- 604 Coco
- 605 Brown
- 606 Grey
- 607 Anthracite
- 608 Black
- 609 Purple
- 610 Turquoise