



Mipolam Elegance - Tile

Generated on 21.08.2019



Detailed description

High performance, monolayer homogeneous vinyl floor covering in tile form.

Features and benefits:

- Available in a range of 33 colours in a 3D effect.
- 100% polyvinyl chloride (PVC).
- Has a modern surface with a matt finish for a long-lasting appearance.
- High abrasion resistance.
- Treated with Evercare™ technology obtained by UV laser cross-linking, and anti-bacterial and fungicidal treatments resulting in easy maintenance and high chemical stain resistance.
- Life expectancy of over 20 years.
- Even surface thickness.
- Resistance to micro-scratches.
- Easy and cost-effective maintenance, with 80% less water and cleaner required.
- Scuff resistant, and doesn't require polishing to maintain its appearance.
- Requires no waxing.
- Total volatile organic compound (TVOC) emissions are 100 times lower than normal requirements.
- CE marked, and manufactured in accordance with EN 14041.

Gerflor Ltd
Wedgnoek House
Wedgnoek Lane
Warwick
Warwickshire
CV34 5AP

Tel: +44 (0)1926 622600

www.gerflor.co.uk
contractuk@gerflor.com

Application:

Suitable for commercial flooring and heavy duty traffic areas.

Installation should be carried out in accordance with BS 8203: 2001, subfloor to be smooth, hard, clean and dry prior to laying, where applicable the subfloor must incorporate a damp proof membrane. Gerflor Ltd recommends the use of Gerfix E120 adhesive. All seams must be hot welded using Gerflor matching weld rod.

Product guidance - As Standard

Size:

608 x 608 mm.

Thickness:

2 mm.

Weight:

2850 g/m².

Gerflor Ltd



Technical characteristics:

- European classification (to BS EN 685): Class 34/ 43.
- Fire rating (to EN 13501-1): Class Bfl-s1.
- Static electrical propensity (to EN 1815): <2 kV.
- Wear resistance (to EN 660-2): $\leq 2 \text{ mm}^3$.
- Wear group (to EN 649): Group T.
- Type binder content (to ISO 10581): Type I.
- Dimensional stability (to EN 434): 0.40%.
- Residual indentation (to EN 433): $\approx 0.03 \text{ mm}$.
- Castor chair test (to EN 425): Type W, Pass.
- Thermal conductivity (to EN 12524): 0.25 W/m·K.
- Colour fastness (to EN 20105-B02): ≥ 6 degree.
- Surface treatment: Evercare™.
- Chemical resistance (to EN 423): Pass.
- Total volatile organic compounds (TVOC) (to ISO 16000-6): $< 10 \mu\text{g}/\text{m}^3$.

Options

Colour:

- 0318 Grape.
- 0319 Quetsche.
- 0321 Olive.
- 0322 Jicama.
- 0323 Nut.
- 0324 Chestnut.
- 0326 Jojoba.
- 0327 Pear.
- 0328 Almond.
- 0329 Hazelnut.
- 0330 Litchi.
- 0331 Plum.
- 0333 Ananas.
- 0336 Acerola.
- 0338 Kiwi.
- 0339 Apple.
- 0340 Jambolan.
- 0341 Bilberry.
- 0342 Blueberry.
- 0343 Pecan.
- 0344 Nutmeg.
-



0347 Mangoustan.

- 0348 Bluetta.
- 0349 Bluecrop.
- 0696 Ginger.
- 0697 Greenstone.
- 0698 Cacao.
- 0699 Banana.
- 0700 Melon.
- 0702 Kumquat.
- 0703 Lime.
- 0704 Raspberry Grey.
- 0705 Patisson.

Product specification

Manufacturer

- Name: Gerflor Ltd
- Web: www.gerflor.co.uk
- Email: contractuk@gerflor.com
- Tel: +44 (0)1926 622600
- Fax: +44 (0)1926 401647
- Address: Wedgnock House, Wedgnock Lane, Warwick, Warwickshire CV34 5AP

Product reference Mipolam Elegance - Tile

Colour

Accessories/ Other requirements