



Connor Sports® Neoshok™

Generated on 10.04.2020

Detailed description

Connor Sports® Neoshok™ is an area-elastic, premium solid hardwood floating studio floor system with high resistance and uniformity. It consists of a vapour barrier, two-stage polyurethane Neoshok pads and two layers of APA plywood subfloor. The maple-finished flooring has the option to sand, seal and receive finishes and game lines. The system has been tested to the international standard EN 14904.

Product guidance - As Standard

Maple strip dimensions (t x w):

20 x 57 mm.

Overall system thickness:

63 mm.

Pads:

Red Neoshok pads, 70 durometer urethane pads.

Abrasion resistance (to ISO 5470-1):

0.07 g.

Shock absorption (to EN 14808):

63.5%.

Ball bounce (to EN 12235):

92%.

Sliding coefficient (to EN 13036-4):

83.

Fire resistance (to EN 13501-1):

Cfl-s1.

Product specification

Manufacturer

- Name: Gerflor Ltd
- Web: www.gerflor.co.uk
- Email: contractuk@gerflor.com
- Tel: +44 (0)1926 622600

Gerflor Ltd



Gerflor Ltd
Wedgnoek House
Wedgnoek Lane
Warwick
Warwickshire
CV34 5AP

Tel: +44 (0)1926 622600

www.gerflor.co.uk
contractuk@gerflor.com



ribaproductselector.com

A building products library for construction industry professionals

NBS Plus

- Fax: +44 (0)1926 401647

- Address: Wedgnoek House, Wedgnoek
Lane, Warwick, Warwickshire CV34 5AP

Product reference Connor Sports® Neoshok™

Colour