



Attraction® Connect - Tile

Generated on 22.10.2019

Detailed description

Attraction® is a semi-flexible tile with a 1.00 mm pure PVC coloured wearlayer. It has a unique dovetail joint which allows rapid loose-lay installation and replacement.

The flooring complies with BS EN 685/649 with a 34-43 classification.

It comes in a standard 635 x 635 mm size and is available in a wide choice of colours. It is suitable for use in areas of high foot traffic and heavy trolley loads and is suitable for retail stores, offices, schools, industrial etc.

It has a Bf1-s1 Fire classification in accordance with standard EN 13501-1.

Product guidance - As Standard

Size:

635 x 635 mm.

Thickness:

5 mm.

Weight:

7460 g/m².

BS EN 649 wear group:

T.

BS EN 685 level of use class:

34 - 43 – Commercial, very heavy – Light industrial, heavy.

Slip resistance class to DIN 51130 (ramp test) – wet with oil:

R10 – The scale runs from R9 to R13, where R9 is the most slippery and R13 the least slippery.

BS EN ISO 717-2 impact sound insulation value:

4 dB.

BS EN 1815 static electricity electrical propensity:

<2 kV.

BS EN 12524 thermal conductivity:

0.25 W/(m.K).

Product specification

Gerflor Ltd



Gerflor Ltd
Wedgnoek House
Wedgnoek Lane
Warwick
Warwickshire
CV34 5AP

Tel: +44 (0)1926 622600

www.gerflor.co.uk
contractuk@gerflor.com



Manufacturer

- Name: Gerflor Ltd
- Web: www.gerflor.co.uk
- Email: contractuk@gerflor.com
- Tel: +44 (0)1926 622600
- Fax: +44 (0)1926 401647
- Address: Wedgnock House, Wedgnock Lane, Warwick, Warwickshire CV34 5AP

Product reference Attraction® Connect - Tile

Colour