



Mipolam Biocontrol - Tile

Generated on 23.08.2019

Detailed description

A densely compacted homogeneous floor covering that is suitable for use in ISO 4 and GMP Class-A cleanrooms. It is resistant to heavy traffic and has outstanding resistance to chemicals. It is 100% recyclable, comprising polymers, non-evaporating plasticizers, stabilizers, mineral and colour fast pigments. The flooring complies with BS EN 649 with a K5 wear rating.

Installation should be carried out in accordance with BS 8203-2001, subfloor to be smooth, hard, clean and dry prior to laying, where applicable the subfloor must incorporate a damp proof membrane. Gerflor Ltd. recommends the use of Gerfix E120 Adhesive. All seams must be hot welded using Gerflor matching weld rod.

Product guidance - As Standard

Size:

608 x 608 mm – 500 m² quantity minimum order, consult manufacturer.

Thickness:

2 mm.

General:

- Particulate emission: ISO 4.
- Cleanability class: 100.
- Micro-organism adhesion: A-C.

Product specification

Manufacturer

- Name: Gerflor Ltd
- Web: www.gerflor.co.uk
- Email: contractuk@gerflor.com
- Tel: +44 (0)1926 622600
- Fax: +44 (0)1926 401647
- Address: Wedgnoek House, Wedgnoek Lane, Warwick, Warwickshire CV34 5AP

Product reference Mipolam Biocontrol - Tile

Colour



Gerflor Ltd
Wedgnoek House
Wedgnoek Lane
Warwick
Warwickshire
CV34 5AP

Tel: +44 (0)1926 622600

www.gerflor.co.uk
contractuk@gerflor.com



ribproductselector.com

A building products library for construction industry professionals

NBS Plus