



## LED Aluminium Stair Edgings

Generated on 21.02.2020

### Detailed description

A range of aluminium stair edgings for housing the Continuity or Interlok Advance LED lighting systems.

The profiles combine hardwearing mill finish aluminium channels with a choice of slip-resistant pvc inserts, and feature a PVC-u tube which houses the LED lighting and fits securely into the channel.

### Product guidance - As Standard

Channel:

– Material:

Aluminium.

– Fixing:

Mechanical and adhesive fix: consult Gradus for further guidance.

### Options

Insert colour:

– Interior:

Jet (LRV: 4.56), Ink (LRV: 4.96), Midnight (LRV: 6.56), Burgundy (LRV: 5.70), Evergreen (LRV: 6.69), Coffee (LRV: 6.05), Ocean (LRV: 8.00), Lead (LRV: 12.77), Steel (LRV: 26.99), Glacier (LRV: 42.09), Canvas (LRV: 53.27), Linen (LRV: 38.59), Buttercup (LRV: 55.54), Snowdrift (LRV: 83.77), Cloud (LRV: 28.57), Poppy (LRV: 10.39).

– Xtra-Grip:

Onyx (LRV: 4.52), Neptune (LRV: 5.03), Umber (LRV: 5.71), Graphite (LRV: 12.56), Quarry (LRV: 24.71), Bamboo (LRV: 45.84), Surf (LRV: 43.58), Concrete (LRV: 37.44), Pumice (LRV: 46.83), Ochre (LRV: 49.97), Frost (LRV: 66.51).

– Xtra-Grip Plus:

Suitable for interior areas where health and safety is a priority with increased roughness. Where stairs may become wet, with an addition of an enhanced insert bind system. Asphalt (LRV: 4.52), Shark (LRV: 5.03), Bark (LRV: 5.71), Mercury (LRV: 12.56), Smoke (LRV: 24.71), Prairie (LRV: 45.84), Air (LRV: 43.58), Dusk (LRV: 37.44), Sandstone (LRV: 46.83), Citrine (LRV: 49.97), Calcite (LRV: 66.51). Not available for ELAF230 or ELAF5150.

### Product specification

Manufacturer

Gradus

# GRADUS

Gradus  
Chapel Mill  
Park Green  
Macclesfield  
Cheshire  
SK11 7LZ

Tel: +44 (0)1625 428922

[www.gradus.com](http://www.gradus.com)  
[imail@gradus.com](mailto:imail@gradus.com)



- Name: Gradus
- Web: [www.gradus.com](http://www.gradus.com)
- Email: [imail@gradus.com](mailto:imail@gradus.com)
- Tel: +44 (0)1625 428922
- Fax: +44 (0)1625 433949
- Address: Chapel Mill, Park Green, Macclesfield, Cheshire SK11 7LZ

**Product reference** LED Aluminium Stair Edgings

**Channel**

- Profiles AS1106L - Ramp back, 74 mm tread, 46.5 mm riser.  
AT718L - 8 mm gauge, 63 mm tread, 41 mm riser.  
ATD71L - 6 mm gauge, 75 mm tread, 43 mm riser.  
ATD121L - 12 mm gauge, 83.5 mm tread, 38 mm riser.  
ATF71L - 6 mm gauge, 75 mm tread, 44 mm riser.  
ATNG71L - 8 mm gauge, 87 mm tread, 47 mm riser.  
ELAF230 - 6.5 mm gauge, 94 mm tread, 30 mm riser. Interior or Xtra-grip insert only.  
ELAF5150 - Black anodized aluminium, 5 mm gauge, 76 mm tread, 25 mm riser. Interior or Xtra-grip insert only.
- Length 2.44 m  
2.75 m  
3.20 m

**Insert**

- Type Interior - For dry internal conditions.  
Xtra-Grip - For areas where stairs may become wet.  
Xtra-Grip Plus - Enhanced slip resistance for areas where health and safety is a priority.

- Colour

**Lighting**

- Effect Continuity (continuous light effect) - Continuous light effect.  
Interlok (pinpoint light effect) - Pinpoint light effect.
- Colour Amber - Interlok only.  
Blue  
Green



**ribaproductselector.com**

A building products library for construction industry professionals

**NBS Plus**

Red  
White