



## 200 x 150 mm shaped box gutter

Generated on 17.01.2020

### Detailed description

200 x 150 mm pressed aluminium shaped profile box gutter.

#### Jointing:

Butyl mastic tape with low modulus silicone sealant at rivet fix through positions is recommended.

#### Fixing:

Stainless steel fasteners are recommended.

### Product guidance - As Standard

#### Dimensions:

- Size (top x front elevation): 200 x 150 mm. Base 140 mm, back face 160 mm.
- Thickness: 2 mm.

### Options

#### Sleeve outlets:

Sleeve outlets are available as an alternative to running outlets. A sleeve outlet consists of a square plate with attached spigot that may be set into the gutter base at any point, giving increased flexibility and cost efficiency. Consult manufacturer for details.

#### Finish/ Colour:

Gutters can be provided in natural mill finish or factory applied polyester powder coatings to BS 6496 and BS 6497. An extensive range of standard colours is available to RAL or BS colours. Other colours may be at an additional cost.

### Product specification

#### Manufacturer

- Name: Guttercrest Ltd
- Web: [www.guttercrest.co.uk](http://www.guttercrest.co.uk)
- Email: [info@guttercrest.co.uk](mailto:info@guttercrest.co.uk)
- Tel: +44 (0)1691 663300
- Fax: +44 (0)1691 663311
- Address: Victoria Road, Oswestry, Shropshire SY11 2HX

Guttercrest Ltd



Guttercrest Ltd  
Victoria Road  
Oswestry  
Shropshire  
SY11 2HX

Tel: +44 (0)1691 663300

[www.guttercrest.co.uk](http://www.guttercrest.co.uk)  
[info@guttercrest.co.uk](mailto:info@guttercrest.co.uk)



<b>Product reference</b>	SBX6 200 x 150 mm shaped profile box gutter
<b>System colour/ Finish</b>	Mill finish Powder coat, colour ____, texture ____ As drawing ____
<b>Gutter</b>	1500 mm, code SBX6/2 3000 mm, code SBX6/1 As drawing ____ Contractor's choice
<b>Fittings</b>	
- Running outlets	None - Optional sleeve outlets may be specified. SBX6/13 running outlet 63 mm round SBX6/14 running outlet 75 mm round SBX6/15 running outlet 100 mm round SBX6/16 running outlet 125 mm round SBX6/17 running outlet 150 mm round SBX6/18 running outlet 75 x 50 mm rectangular SBX6/19 running outlet 75 mm square SBX6/20 running outlet 100 x 75 mm rectangular SBX6/21 running outlet 100 mm square SBX6/22 running outlet 150 x 100 mm rectangular SBX6/23 running outlet 150 x 150 mm square As drawing ____ Contractor's choice
- Angles	SBX6/3 90° external angle SBX6/4 90° internal angle SBX6/5 135° external angle SBX6/6 135° internal angle SBX6/7 ____° irregular external angle - Bespoke angles available. SBX6/8 ____° irregular internal angle - Bespoke angles available. As drawing ____ Contractor's choice
- Stop ends	SBX6/10 right hand stop end SBX6/11 left hand stop end As drawing ____ Contractor's choice
<b>Brackets/ Rafter arms</b>	None - Manufacturer recommends direct fixing of this gutter size. SBX6/29 side rafter bracket SBX6/30 top rafter bracket - Manufacturer advises against use of this bracket type. SBX6/31 mortar bracket As drawing ____ Contractor's choice



**rib**productselector.com

A building products library for construction industry professionals

**NBS Plus**