



## 100 x 75 mm traditional socketed rectangular downpipe

Generated on 21.02.2020

### Detailed description

100 x 75 mm extruded aluminium traditional style rectangular downpipe, with cast aluminium sockets.

### Fixing:

Stainless steel fasteners are recommended.

### Product guidance - As Standard

#### Dimensions:

- Socket length: 105 mm.
- Wall thickness: 2 mm.

### Options

#### Finish/ Colour:

Downpipes can be provided in natural mill finish or factory applied polyester powder coatings to BS 6496 and BS 6497. An extensive range of standard colours is available to RAL or BS colours. Other colours may be at an additional cost.

### Product specification

#### Manufacturer

- Name: Guttercrest Ltd
- Web: [www.guttercrest.co.uk](http://www.guttercrest.co.uk)
- Email: [info@guttercrest.co.uk](mailto:info@guttercrest.co.uk)
- Tel: +44 (0)1691 663300
- Fax: +44 (0)1691 663311
- Address: Victoria Road, Oswestry, Shropshire SY11 2HX

<b>Product reference</b>	RW43G 100 x 75 mm traditional socketed rectangular downpipe
<b>System colour/ Finish</b>	Mill finish Powder coat, colour ____, texture ____ As drawing ____
<b>Pipes</b>	1000 mm, code RW43G/5 - Socket with ears.

Guttercrest Ltd



Guttercrest Ltd  
Victoria Road  
Oswestry  
Shropshire  
SY11 2HX

Tel: +44 (0)1691 663300

[www.guttercrest.co.uk](http://www.guttercrest.co.uk)  
[info@guttercrest.co.uk](mailto:info@guttercrest.co.uk)



1500 mm, code RW43G/4 -

Socket with ears.

1800 mm, code RW43G/3 -

Socket with ears.

3000 mm, code RW43G/1 -

Socket with ears.

As drawing \_\_\_\_

Contractor's choice

## Fittings

### - Access pipes

None

RW43G/8 access pipe with cover plate - Socket with ears.

RW43G/9 spare cover plate

As drawing \_\_\_\_

Contractor's choice

### - Branches

None

RW43G/11 112.5° left hand single branch - Primary socket with ears.

RW43G/11 112.5° right hand single branch - Primary socket with ears.

As drawing \_\_\_\_

Contractor's choice

### - Bends

None

RW43G/21 112.5° left hand bend - Socket without ears.

RW43G/21 112.5° right hand bend - Socket without ears.

RW43G/22 112.5° left hand bend - Socket with ears.

RW43G/22 112.5° right hand bend - Socket with ears.

As drawing \_\_\_\_

Contractor's choice

### - Offsets

None

RW43G/23 plinth offset, \_\_\_\_ mm projection - Bespoke offset bend.

As drawing \_\_\_\_

Contractor's choice

### - Swan necks

None

RW43G/25 one piece, \_\_\_\_ mm projection - Bespoke one piece swan neck bend; without ears.

RW43G/26 two piece - Maximum 300 mm projection; without ears.

RW43G/27 two piece - Maximum 450 mm projection; without ears.

RW43G/28 two piece - Maximum 600 mm projection; without ears.

RW43G/29 two piece - Maximum 900 mm projection; without ears.

RW43G/30 two piece - Maximum 1200 mm projection; without ears.

RW43G/31 two piece, \_\_\_\_ mm



projection - Bespoke two piece  
swan neck bend, minimum  
projection 115 mm. Without ears.  
As drawing \_\_\_\_  
Contractor's choice

- Connectors (loose sockets)

None  
RW43G/12 connector - Without  
ears.  
RW43G/13 connector - With ears.  
As drawing \_\_\_\_  
Contractor's choice

- Shoes

None  
RW43G/10 shoe - Socket with  
ears.  
As drawing \_\_\_\_  
Contractor's choice

**Hoppers**

None  
RWH207 rectangular hopper, 100  
x 75 mm rectangular outlet  
RWH209 ornate rectangular  
hopper, 100 x 75 mm rectangular  
outlet  
As drawing \_\_\_\_  
Contractor's choice

**Pipe clips and brackets**

RW43G/15 collar bracket - With  
ears.  
As drawing \_\_\_\_  
Contractor's choice