



Reduc Foundation

Generated on 16.12.2018

Detailed description

High performance structural or overlay acoustic flooring boards designed to damp vibration and attenuate airborne and impact noise passing through floors. They comprise two layers of moisture-resistant chipboard, separated by visco-elastic sound damping strips, with an acoustic felt on the underside.

The moisture-resistant upper surface means Reduc Foundation and Foundation Extra can be used throughout the building, including kitchens and bathrooms. When used as an overlay on existing floors the acoustic felt on the underside will contour over minor irregularities on the floor surface. Suitable for use on new and existing timber and concrete floors.

Product guidance - As Standard

Size (l x w):

2400 x 600 mm.

Weight:

20.5–23.6 kg/m².

Laid area per board:

1.44 m².

Product specification

Manufacturer

- Name: H & H Acoustic Technologies
- Web: www.acoustictechnologies.co.uk
- Email: info@acoustictechnologies.co.uk
- Tel: +44 (0)1536 270450
- Address: 23 Princewood Road, Corby NN17 4AP

Product reference Reduc Foundation - 35 mm thickness, 20.5 kg/m², for 450 mm joist centres.
Reduc Foundation Extra - 39 mm thickness, 23.6 kg/m², for 600 mm joist centres.



H & H Acoustic Technologies
23 Princewood Road
Corby
NN17 4AP

Tel: +44 (0)1536 270450

www.acoustictechnologies.co.uk
info@acoustictechnologies.co.uk



ribaproductselector.com

A building products library for construction industry professionals

NBS Plus