



5000 Series (Stainless Steel) Single Cover

Generated on 07.04.2020



Detailed description

Stainless steel light duty floor access cover for pedestrian traffic, including wheeled trolleys, sack trucks, etc.

Features:

- Covers can be fitted quickly and unobtrusively into all types of hard floor finish: ceramic tiles, marble, terrazzo, resin or parquet.
- Cover sections are tapered for easy removal and are precision-made to avoid distortion.
- Double seals available.
- Lifting blocks are anchored to the inner frame. Stainless steel securing bolts are stiletto heel proof.

Manufactured in accordance with BS EN ISO 9001.

Product guidance - As Standard

Material:

Show edge manufactured from stainless steel with steel baseplate and reinforcement.

Depth:

50 mm.

Weight (when filled):

90 kg/m².

Overall frame size:

Clear opening size plus 130 mm.

Product specification

Manufacturer

- Name: Howe Green Ltd
- Web: www.bilcouk.co.uk
- Email: info@howegreen.co.uk
- Tel: +44 (0)1920 463230
- Fax: +44 (0)1920 463231
- Address: Marsh Lane, Ware, Hertfordshire SG12 9QQ

Howe Green Ltd

Howe Green Ltd
Marsh Lane
Ware
Hertfordshire
SG12 9QQ

Tel: +44 (0)1920 463230

www.bilcouk.co.uk
info@howegreen.co.uk



Product reference	5000 Series (Stainless Steel) Single Cover
Clear opening size (w x l)	As drawing - Insert reference, available 150– 750 x 150–750 mm.
Material	
- Cover and frame	Stainless steel, grade 1.4301 (304) - Standard. Stainless steel, grade 1.4401 (316)
- Base plate	Galvanized steel - Standard. Stainless steel, grade 1.4301 (304) Stainless steel, grade 1.4401 (316)
Sealing	Double sealed with socket head securing bolts Unsealed with blanking bolts
Fire rating	None One hour - To BS 476-20.
Lifting points	Not required Barrel only Inset
Sets of combined lifting/ securing keys	Not required Required
Cover skate lifting device	Not required Required