



## 1050 Series (Stainless Steel) Single Cover

Generated on 07.04.2020



### Detailed description

Stainless steel heavy duty floor access cover for up to 6.5 tonne pneumatic tyre wheel load (C250).

#### Features:

- Specifically designed for use in external pedestrianised areas where vehicular access is required.
- Covers can be fitted quickly and unobtrusively into all types of hard floor finish: concrete or natural stone.
- Unique cover sections are tapered for easy removal and are precision-made to avoid distortion.
- Double seals available.
- Lifting blocks are anchored to the inner frame. Stainless steel securing bolts are stiletto heel proof.
- Provides easy access to under floor services using lifting keys.

Manufactured in accordance with BS EN ISO 9001.

### Product guidance - As Standard

#### Material:

Show edge manufactured from stainless steel with steel baseplate and reinforcement.

#### Depth:

105 mm.

#### Weight (when filled):

220 kg/m<sup>2</sup>.

#### Overall frame size:

Clear opening size plus 130 mm.

### Product specification

#### Manufacturer

- Name: Howe Green Ltd
- Web: [www.bilcouk.co.uk](http://www.bilcouk.co.uk)
- Email: [info@howegreen.co.uk](mailto:info@howegreen.co.uk)
- Tel: +44 (0)1920 463230

Howe Green Ltd

Howe Green Ltd  
Marsh Lane  
Ware  
Hertfordshire  
SG12 9QQ

Tel: +44 (0)1920 463230

[www.bilcouk.co.uk](http://www.bilcouk.co.uk)  
[info@howegreen.co.uk](mailto:info@howegreen.co.uk)



- Fax: +44 (0)1920 463231

- Address: Marsh Lane, Ware, Hertfordshire SG12 9QQ

<b>Product reference</b>	1050 Series (Stainless Steel) Single Cover
<b>Cover and frame material</b>	Stainless steel, grade 1.4301 (304) - Standard. Stainless steel, grade 1.4401 (316)
<b>Sealing</b>	Double sealed with socket head securing bolts Unsealed with blanking bolts
<b>Fire rating</b>	None Three hours - To BS 476-20.
<b>Support beam pockets</b>	Not required Recessed - For use where support beams are required. Surface mounted - For use where support beams are required.
<b>Lifting points</b>	Not required Barrel only Inset
<b>Sets of combined lifting/ securing keys</b>	Not required Required
<b>Cover skate lifting device</b>	Not required Required