



HSE 75 Series (Aluminium) Multipart Cover

Generated on 07.04.2020



Detailed description

Aluminium medium duty floor access covers for up to 5 tonne pneumatic tyre wheel load (cars and light delivery vehicles).

Features:

- Covers can be fitted quickly and unobtrusively into all types of hard floor finish: ceramic tiles, marble, terrazzo, concrete, resin, wood or parquet.
- Unique patented cover sections are tapered for easy removal, frame sections give a good key to bedding mortar.
- Covers are precision-made to avoid distortion.
- Top edge seal on aluminium covers helps prevent dirt, grout or grinding waste penetrating joint between cover and frame.
- Double seals available.
- Lifting blocks are anchored to the inner frame. Stainless steel securing bolts are stiletto heel proof.
- Easy to install ensuring minimum disruption.

Manufactured in accordance with BS EN ISO 9001.

Product guidance - As Standard

Material:

Show edge manufactured from aluminium with steel baseplate and reinforcement. Galvanized carbon steel support beams and pockets (where necessary).

Depth:

75 mm.

Required opening force (when filled):

20 kg.

Sealing:

Double sealed with socket head securing bolts complete with all necessary removable sealing cross-members and support beams.

Hinges:

Access covers fitted with multi-link hinges.

Product specification

Manufacturer

Howe Green Ltd

Howe Green Ltd
Marsh Lane
Ware
Hertfordshire
SG12 9QQ

Tel: +44 (0)1920 463230

www.bilcok.co.uk
info@howegreen.co.uk



- Name: Howe Green Ltd
- Web: www.bilcouk.co.uk
- Email: info@howegreen.co.uk
- Tel: +44 (0)1920 463230
- Fax: +44 (0)1920 463231
- Address: Marsh Lane, Ware, Hertfordshire SG12 9QQ

Product reference	HSE 75 Series (Aluminium) Multipart Cover
Design	As drawing - Insert reference.
Clear opening width	As drawing - Insert reference, available 550–1000 mm.
Material	
- Base plate	Galvanized steel - Standard. Stainless steel, grade 1.4301 (304) Stainless steel, grade 1.4401 (316)
- Gas springs	Carbon steel, powder coated - Standard. Stainless steel, grade 1.4401 (316)
Fire rating	None Two hours - To BS 476-20.
Support beam pockets	Not required Recessed - For use where support beams are required. Surface mounted - For use where support beams are required.
Underside release latch	Not required Required
Sets of combined lifting/ securing keys	Not required Required