



ARDEX P 51

Generated on 09.07.2020

Detailed description

ARDEX P 51 is used to prepare internal surfaces to receive cement-based levelling compounds, adhesives, screeds, as well as plaster-based materials, improving adhesion and inhibiting penetration of water in intermittently damp locations. It is used as a pore sealer on floor surfaces to prevent air bubbles rising through subsequently applied sub-floor smoothing and levelling compounds and to prolong their flow life and workability. Only for use as a primer on floors that are dry and have an effective damp proof membrane.

ARDEX P 51 can be diluted with an equal volume of water to prepare a grouting slurry for bonded screeds, when mixed with ARDEX A 23 or A 35 Screeds.

Product specification

Manufacturer

- Name: ARDEX UK Ltd
- Web: ardex.co.uk
- Email: info@ardex.co.uk
- Tel: +44 (0)1440 714939
- Fax: +44 (0)1440 716667
- Address: Homefield Road, Haverhill, Suffolk CB9 8QP

Product reference ARDEX P 51 Concentrated Water-Based Primer and Bonding Agent



ARDEX UK Ltd
Homefield Road
Haverhill
Suffolk
CB9 8QP

Tel: +44 (0)1440 714939

ardex.co.uk
info@ardex.co.uk



ribproductselector.com

A building products library for construction industry professionals

NBS Plus