



Brise Soleil Solar Shading Grilles

Generated on 21.02.2020

Detailed description

Aluminium dual purpose walkway/ sunscreen providing a versatile metal grating design that delivers excellent performance in a multitude of applications.

Brise Soleil uses curved alternate louvre extrusions to provide the same high performance as the Louvredek system, either as a combined walkway/ sunscreen or solely as a sunscreen. The system can be installed anywhere required: underfoot, on an angle or overhead.

It is an ecologically friendly product that is also lightweight yet extremely strong. Its modular connection system requires no welding for assembly on site.

Features and benefits:

- Lightweight.
- Environmentally friendly - 100% recyclable.
- Maintenance free.
- Aesthetically pleasing.
- Non-toxic - inert material.
- Non-combustible.
- Corrosion-free.
- Includes a lifetime guarantee.

Applications:

For walkway and sunscreen use.

Product guidance - As Standard

Material:

Aluminium alloy (6063 T4 and T6).

Bar:

- Thickness: 3 mm (louvre extrusion has a width of 24 mm).
- Spacing: Louvre extrusion: 60 mm; Flat bar: 100 mm.
- Depth: Louvre extrusion: 73 mm; Flat bar: 25 mm.

Louvre extrusion angle:

62°.

Sun shade ratio:

1:1.88.

NEACO Ltd



neaco

norton engineering alloys co ltd

NEACO Ltd

Norton Grove Industrial Estate
Norton
Malton
North Yorkshire
YO17 9HQ

Tel: +44 (0)1653 695721

www.neaco.co.uk
sales@neaco.co.uk



Product specification

Manufacturer

- Name: NEACO Ltd
- Web: www.neaco.co.uk
- Email: sales@neaco.co.uk
- Tel: +44 (0)1653 695721
- Fax: +44 (0)1653 600418
- Address: Norton Grove Industrial Estate, Norton, Malton, North Yorkshire YO17 9HQ

- Product reference**
- SS 3/73 - Brise Soleil Sunscreen, louvre extrusions only, should not be walked on, 11 kg/m².
 - SWP 25/3/73 - Brise Soleil Walkway, louvre extrusions and plain flat bars, 14.3 kg/m².
 - SWS 25/3/73 - Brise Soleil Walkway, louvre extrusions and serrated flat bars, 14.6 kg/m².

Panel size (w x l) [_____]

Finish/ colour Mill - Standard.
Anodized

NEACO Fixing Clamps Not required
Required