



Pilkington Suncool™ High Performance Solar Control with Low-E Thermal Insulation



PILKINGTON

Generated on 30.05.2020

Detailed description

Maximum/ Minimum pane size:

Depends on glass type, thickness, colour and application - refer to Pilkington.

Options

Thickness:

6 and 10 mm (other thicknesses may be available to special order).

Coating colours:

Available in 9 tints. Coating can be applied to toughened glass.

Product specification

Manufacturer

- Name: Pilkington United Kingdom Limited
- Web: www.pilkington.co.uk
- Email: pilkington@respond.uk.com
- Tel: +44 (0)1744 692000
- Fax: +44 (0)1744 692880
- Address: European Technical Centre, Hall Lane, Westhead, Lathom, Lancashire L40 5UF

Product reference	Pilkington Suncool™ High Performance Solar Control with Low-E Thermal Insulation
Type	Annealed Toughened
Thickness	6 10
Colour	Blue Brilliant Brilliant Blue Bronze Clear Green Grey Neutral

Pilkington United Kingdom Limited

European Technical Centre

Hall Lane

Westhead

Lathom

Lancashire

L40 5UF

Tel: +44 (0)1744 692000

www.pilkington.co.uk

pilkington@respond.uk.com



ribaproductselector.com

A building products library for construction industry professionals

NBS Plus

Silver