



Rockfon® VertiQ® Wall Panel

Generated on 24.02.2020

Detailed description

Highly sound absorbent, acoustic wall panels.

Features and benefits:

- Class A sound absorption and Class A2-s1,d0 fire safety.
- Attractive to the visible side, with a durable, fine-woven surface.
- Impact resistant.
- Can be installed full height, either horizontally or vertically, with no limits to wall dimensions.
- Easy to clean with a vacuum cleaner.
- Provides design freedom to suit project requirements.
- Available in four colours.
- Hygienic; stone wool provides no sustenance to micro-organisms.
- Includes painted edges.
- Can be fully recycled.

Application:

Suitable for use in areas including:

- Education, e.g. classrooms.
- Sports activity areas.
- Industry.
- Office.
- Leisure.

Consult manufacturer for recommended installation systems. Can be used in swimming pools, provided it is not exposed to condensation, splashing water or droplets.

Product guidance - As Standard

Thickness:

40 mm.

Surface finish:

- Visible side: Durable, fine-woven surface.
- Rear side: Back fleece.

Sound absorption:

1.00 α_w . Class A.

Rockfon



Rockfon
14th Floor
Chiswick Tower
389 Chiswick High Road
London
W4 4AL

Tel: +44 (0)208 2227457

www.rockfon.co.uk
info@rockfon.co.uk



Reaction to fire:

A2-s1,d0.

Humidity and sag resistance:

Dimensionally stable, even at humidity levels of up to 100% RH.

Light reflection:

- Black: 5%.
- Grey: 33%.
- Light grey: 61%.
- White: 72%.

Impact resistance:

- Rockfon VertiQ® C and Rockfon VertiQ® A have been tested for impact resistance in accordance with DIN 18032 part 3, and fulfil the demands for handball ball throwing (restrictedly safe against ball throwing).
- Rockfon System VertiQ® HAT A Wall gives additional protection of Rockfon VertiQ® A panels by HAT steel profile, and can be used in areas subjected to occasional impact.
- The impact resistance of Rockfon System VertiQ® HAT A Wall and Rockfon System VertiQ® C Wall is high, however, it is not recommended for use in areas which are subjected to continuous high levels of impact.
- The woven surface of Rockfon VertiQ® panels provides enhanced resistance to perforation, tested in accordance with NF P 08-301.

Cleaning:

The surface can be vacuum cleaned with a soft brush attachment.

Product specification

Manufacturer

- Name: Rockfon
- Web: www.rockfon.co.uk
- Email: info@rockfon.co.uk
- Tel: +44 (0)208 2227457
- Fax: +44 (0)208 2227458
- Address: 14th Floor, Chiswick Tower, 389 Chiswick High Road, London W4 4AL

Product reference Rockfon® VertiQ® Wall Panel

Module size 1200 x 1200 mm - 5.2 kg/m².
2400 x 600 mm - 6.4 kg/m².



2700 x 1200 mm - 5.2 kg/m².

Colour

Black
Grey
Light grey
White

Edges

A HAT - Available with 1200 x 1200 mm and
2700 x 1200 mm only.
A24 - Available with 1200 x 1200 mm and
2700 x 1200 mm only.
C - Available with 2400 x 600 mm only.