



Eco Plus

Generated on 14.10.2019

Detailed description

A microprocessor controlled instantaneous domestic water heater with thermally insulated stainless steel plate heat exchanger and pipework (for warm start) and integral charge pump and non-return valve for use in family homes. The surface unit has a one piece white metal cover. Whilst it is designed to be installed in close proximity to taps and operated without a circulation pump, it can be used in conjunction with an external circulation pump.

Product guidance - As Standard

Size (w x h x d):

480 x 800 x 160 mm.

Weight:

14 kg.

Number of heat exchange plates:

14.

Nominal output:

85 kW.

Hot water temperature:

10–45 °C.

Volume flow at 45 °C:

35 L/min.

Maximum operating pressure:

3 bar.

Pipework connections:

Ball valve Rp 1.

Operating voltage:

230 V AC

Protection class:

IP54.

Product specification

Schueco UK Ltd

SCHÜCO

Schueco UK Ltd

Whitehall Avenue

Kingston

Milton Keynes

Buckinghamshire

MK10 0AL

Tel: +44 (0)1908 282111

www.schueco.co.uk
mkinfobox@schueco.com



Manufacturer

- Name: Schueco UK Ltd
- Web: www.schueco.co.uk
- Email: mkinfobox@schueco.com
- Tel: +44 (0)1908 282111
- Fax: +44 (0)1908 282124
- Address: Whitehall Avenue, Kingston, Milton
Keynes, Buckinghamshire MK10 0AL

Product reference Eco Plus

Mounting Surface
Concealed