



## AP Rainscreen Facade Aluminium Rivets

Generated on 11.07.2020

### Detailed description

The AP rivets have a 5.0 mm diameter body manufactured from Aluminium (AlMg5) with an austenitic stainless steel (EN 1.4541) mandrel.

The shallow domed head is available in diameters of 11, 14 and 16 mm and may be painted to match the rainscreen panels.

The AP rivets are installed through the rainscreen panel which has a clearance hole and into the steel or aluminium support section which has to be predrilled 5.1 mm.

### Warranty:

Up to 25 years (period to be confirmed and agreed specific to the project).

### Product guidance - As Standard

#### Material:

Rivet body is manufactured from Aluminium (AlMg5) and the mandrel from austenitic stainless steel (Grade EN 1.4541 and are therefore suitable for all corrosivity categories; C1–C5 as defined in BS EN 12944.

### Options

#### Colour/ Finish:

Rivet head can be coloured to order in the standard RAL and NCS colours to match rainscreen facade panels.

#### Material:

Consult manufacturer for suitability with swimming pool applications.

### Product specification

#### Manufacturer

- Name: SFS Group Fastening Technology Ltd
- Web: [www.sfsintec.co.uk](http://www.sfsintec.co.uk)
- Email: [enquiries@sfs.biz](mailto:enquiries@sfs.biz)
- Tel: +44 (0)330 0555 888
- Fax: +44 (0)113 2085539
- Address: 153 Kirkstall Road, Leeds, West Yorkshire LS4 2AT

**Product reference** AP rivets

SFS Group Fastening Technology Ltd



**SFS Group Fastening Technology Ltd**

153 Kirkstall Road

Leeds

West Yorkshire

LS4 2AT

Tel: +44 (0)330 0555 888

[www.sfsintec.co.uk](http://www.sfsintec.co.uk)

[enquiries@sfs.biz](mailto:enquiries@sfs.biz)



**Head diameter** AP11 - 11 mm diameter.  
AP14 - 14 mm diameter.  
AP16 - 16 mm diameter.

**Rivet length** [ ]

**Colour/ Finish** [ ]