



Bituthene® 8000 HC

Generated on 12.12.2019

Detailed description

Bituthene® 8000 HC is an advanced self-adhesive, solar reflective, flexible water and vapour proof membrane, designed for sub-structures in hot climates. It can be used horizontally or vertically to protect basements and other critical sub-structures from the effects of aggressive ground conditions and water tables.

Substrate:

Monolithic concrete blinding is preferred which should be regular, smooth and free of loose aggregate and sharp protrusions.

Application:

Brush the membrane onto the surface to ensure good initial bond and exclude air.

Joint laps:

Minimum laps of 50 mm are recommended.

Product guidance - As Standard

Thickness:

1.5 mm.

Options

Primer:

Bituthene® Primer B1 is used to prepare vertical and sloping surfaces and suspended slabs.

Continuity sealant:

Bituthene® LM is a high performance liquid membrane providing waterproof continuity at angles and for detailing terminations at pile caps and pipe penetrations.

Product specification

Manufacturer

- Name: GCP Applied Technologies
- Web: www.gcpat.com
- Email: uksales@gcpat.com
- Tel: +44 (0)1753 490000
- Fax: +44 (0)1753 490001

GCP Applied Technologies



gcp applied technologies

GCP Applied Technologies

580/1 Ipswich Road
Slough
Berkshire
SL1 4EQ

Tel: +44 (0)1753 490000

www.gcpat.com
uksales@gcpat.com



- Address: 580/1 Ipswich Road, Slough, Berkshire SL1 4EQ

Product reference Bituthene® 8000 HC

Primer Not required
Bituthene® B1 primer

Continuity sealant Not required
Bituthene® LM