



4880 Roller Blind System

Generated on 22.10.2019



Detailed description

4880 Roller Blind System is a wall, ceiling or recessed mounted, electrically operated roller blind, based on the 4840 System, designed for very heavy duty applications. It is made to measure and supplied ready assembled.

Varied fixing possibilities to wall, ceiling or recess are available. It has easy front loading into snap brackets and bracket covers are available for neater appearance outside recess.

Motor position is preferably situated on the left side. Blind size is determined by overall size and fabric weight.

For systems under 4000 mm wide, on-site adjustment of the headrail is available to prevent rolling-off caused by minor fabric problems. Optional side guide wires are available.

The blinds incorporate a stainless steel bracket set with vertical adjustment facility. Pre-fitted hook-on stainless steel plates take the weight of the blind whilst the fitters carry out final positioning of the brackets. The latter are each adjustable sideways by up to 18 mm. The blind is then conventionally fitted from below (especially important in a blind box situation).

Headrail support tube:

- Ref 4901: Dimensions – 80 mm diameter; maximum 4000 mm wide.
- Ref 4957: Dimensions – 110 mm diameter; for systems over 4000 mm wide.

System type:

- Single: Complete with end brackets and support covers.
- Double system: Complete with end and centre brackets, end brackets support cover and centre brackets support covers.

Product guidance - As Standard

Headrail:

Support tube material/ colour: Silver anodized aluminium.

Side guide wires:

System includes: Top fastener Ref 4946, Wire rope Ref 4948, Bracket Ref 3036 and Bottom fastener Ref 4947.

Options

Blind dimensions

- Maximum width: 5000 mm.
- Maximum drop: 12000 mm.

Silent Gliss Ltd

Silent Gliss Ltd
Pyramid Business Park
Poorhole Lane
Broadstairs
Kent
CT10 2PT

Tel: +44 (0)1843 863571

www.silentgliss.co.uk
info@silentgliss.co.uk



- Maximum surface area: 36 m².

Blind material and colour:

- A wide range of Silent Gliss® fabrics is available; select from SG range. Consult manufacturer for details.
- Blind size is determined by overall size and fabric weight.

Wall switch:

Non-latching white plastic switch available in one, two, three, four, five and six gang options; consult manufacturer for details.

Product specification

Manufacturer

- Name: Silent Gliss Ltd
- Web: www.silentgliss.co.uk
- Email: info@silentgliss.co.uk
- Tel: +44 (0)1843 863571
- Fax: +44 (0)1843 864503
- Address: Pyramid Business Park, Poorhole Lane, Broadstairs, Kent CT10 2PT

Product reference	4880 Roller Blind System
Dimensions	As drawing ____ As schedule ____
Blind material/ Colour	As schedule ____
Bottom bar material/ Colour	White powder coated aluminium - Standard version. Black anodized aluminium Silver anodized aluminium
Motor	
- Type	230V/ 50 Hz 115V/ 60 Hz
- Operation	Radio Remote Control System Wall mounted white plastic switch
Accessories	[Not required] [Bracket cover (for 3134) Ref 3133] [Extended bottom bracket for side guide wire Ref 3134] [Side guide wires]