



Powershield Security Doorsets

Generated on 13.11.2019

Detailed description

The Security Doorset has been designed to provide protection and withstand attacks using simple hand tools through to prolonged attacks with a range of power tools in accordance with LPS 1175.

All doorsets are available with a wide range of options and sizes, includes integral astagal and security hinges and supplied with factory-fitted hardware for ease of installation.

Additional information for this product is available from:

<https://www.assaabloy.co.uk/en/local/uk/product/all-products/security-doors1/powershield-steel-doorsets--glazing-/powershield-security-doorsets/>

Options

Material:

- Colour/ Finish:

A wide range BS and RAL polyester powder coated colours are available, consult manufacturer for more details or refer to colour chart.

Ironmongery:

An extensive range of ironmongery is available from ASSA ABLOY, consult manufacturer for exact details.

Product specification

Manufacturer

- Name: ASSA ABLOY Opening Solutions UK & Ireland
- Web: www.assaabloy.co.uk
- Email: emily.benson@assaabloy.com
- Tel: +44 (0)1902 364120
- Fax: +44 (0)1902 364000
- Address: ASSA ABLOY UK Ltd, School Street, Willenhall, West Midlands WV13 3PW

- | | |
|--------------------------|---|
| Product reference | Personnel Security - 1.2 mm thick door skin with honeycomb or mineral wool core.
Class 1 - 1.5 mm thick door skin with honeycomb or mineral wool core.
Class 2 - 2.0 mm thick door skin with honeycomb or mineral wool core.
Class 3 - 1.5 mm thick door skin with |
|--------------------------|---|

ASSA ABLOY

ASSA ABLOY Opening Solutions UK & Ireland
ASSA ABLOY UK Ltd
School Street
Willenhall
West Midlands
WV13 3PW

Tel: +44 (0)1902 364120

www.assaabloy.co.uk
emily.benson@assaabloy.com



honeycomb or mineral wool core.
Class 4 - 1.5 mm thick door skin with vertical steel stiffened honeycomb or mineral wool core.
Prison - Epoxy powder primed finish only.
Meets British Home Office and Irish Prison Service Standards.

Material

- Type Galvatite ZF Galvanneal - Standard, 1.2–2 mm thick.
Stainless steel, grade 1.4301 (304) - Optional, 1.2–4 mm thick.
Stainless steel, grade 1.4401 (316) - Optional, 1.2–4 mm thick.

- Thickness [_____]

- Colour/ Finish Epoxy powder primed
Polyester powder coated - Insert requirements.
Rimex patterned - Stainless steel only.
Satin polish 180–240 grit - Stainless steel only.

Leaf core Honeycomb
Medium density mineral wool
Solid timber - Class 4 only.
Vertical steel stiffened honeycomb - Class 3 only.

Frame profile Double rebate
Single rebate
Standard prison frame
Two part wrap around
As drawing
As schedule

Ironmongery [_____]