



Visqueen High Performance (HP) Vapour Barrier



Generated on 11.12.2019

Detailed description

Visqueen High Performance (HP) Vapour Barrier is used to omit the risk of interstitial condensation within a structure as well as improving the general airtightness of the building. It restricts the passage of warm, moist air from within the building from permeating into the structure or the roof and is commonly used within timber frame housing as well as commercial buildings. It is a high quality multi layer reinforced LDPE membrane with an aluminium core and is designed for use in roofs, walls and floors subjected to humidity levels less than 60% at 20°C (BS 5250: 2002 class 4 and 5 conditions), e.g. domestic dwellings with high occupancy, sports halls, swimming pools, communal shower areas, laundries, canteens and buildings with wet industrial processes.

For installation and test results information please refer to the manufacturer's datasheet.

Product guidance - As Standard

Width:

1.6 m.

Product specification

Manufacturer

- Name: Visqueen
- Web: www.visqueen.com
- Tel: +44 (0) 333 202 6800
- Fax: +44 (0) 333 202 6886
- Address: Visqueen ,Heanor Gate Industrial Estate,Heanor,Derbyshire DE75 7RG

Product reference	Visqueen High Performance (HP) Vapour Barrier
Roll length	30 m 60 m Contractor's choice
Accessories	[Double-sided Bonding Tape] [Vapour Edge Tape] [Vapour Tape]

Visqueen
Visqueen
Heanor Gate Industrial Estate
Heanor
Derbyshire
DE75 7RG

Tel: +44 (0) 333 202 6800

www.visqueen.com



ribaproductselector.com

A building products library for construction industry professionals

NBS Plus