



Danopanel

Generated on 10.04.2020

Detailed description

An acoustic lining panel for use in buildings with high acoustic requirements. The panel is installed with hidden fixing directly to wooden laths or furring channel S25/85.

Acoustic performance:

Consult Knauf Danoline for details.

Product guidance - As Standard

Size:

600 x 600 mm.

Thickness:

12.5 mm.

Grid type:

Concealed.

Primary grid centres:

300 mm.

Secondary grid centres:

Not applicable.

Options

Finish/ Colour:

- White painted (NCS 0700) is standard.
- Other colours and treatments are available on request.

Access

- Consult Knauf Danoline for recommendations and details.

Product specification

Manufacturer

- Name: Knauf
- Web: www.knauf.co.uk
- Email: technical@knauf.co.uk

Knauf



Knauf
Kemsley Fields Business Park
Sittingbourne
Kent
ME9 8SR

Tel: +44 (0)1795 424499

www.knauf.co.uk
technical@knauf.co.uk



- Tel: +44 (0)1795 424499
- Fax: +44 (0)1795 416261
- Address: Kemsley Fields Business Park, Sittingbourne, Kent
ME9 8SR

Product reference Danopanel

Perforations Acoustic Globe (G1)
Acoustic Micro (M1)
Acoustic Quadril (Q1)
Acoustic Tangent (T1)
Plain Regula (R)

Finish/ Colour White