



## Adesivil D3

Generated on 24.01.2020



### Detailed description

A nonhazardous, solvent free adhesive based on vinyl acetate resins dispersed in water. Produces transparent, water resistant film when dry.

Class D3 to BS EN 204/ 205.

Application temperature: Above 15°C.

Fast setting; flooring is ready for traffic after 12–24 hours.

### Where to use:

- Bonding of tongue and groove prefinished wood sections.
- Bonding of tongue and groove laminates and particleboard panels.
- Bonding in general of small sections of wood.
- Bonding of external door and window frames, and kitchen and bathroom cabinets exposed to wetting.

### Product specification

#### Manufacturer

- Name: Mapei (UK) Ltd
- Web: [www.mapei.co.uk](http://www.mapei.co.uk)
- Email: [sales@mapei.co.uk](mailto:sales@mapei.co.uk)
- Tel: +44 (0)121 508 6970
- Fax: +44 (0)121 508 6960
- Address: Mapei House, Steel Park Road, Halesowen, West Midlands B62 8HD

**Product reference** Adesivil D3

**Mapei (UK) Ltd**  
Mapei House  
Steel Park Road  
Halesowen  
West Midlands  
B62 8HD

Tel: +44 (0)121 508 6970

[www.mapei.co.uk](http://www.mapei.co.uk)  
[sales@mapei.co.uk](mailto:sales@mapei.co.uk)



**ribaproductselector.com**

A building products library for construction industry professionals

**NBS Plus**