



## Ultrabond Eco Fix

Generated on 07.04.2020



### Detailed description

Solvent-free, non staining acrylic based pressure sensitive adhesive with very low emissions of volatile organic compounds (VOC). Used for both permanent and release bonding of a wide range of floor coverings.

### Application:

- For the permanent bonding of PVC/vinyl sheet and tiles, most carpets, smooth-backed thin rubber sheet and tile.
- Pressure sensitive adhesive for the release bonding of underlays, carpet tiles, vinyls and dimensionally stable carpet.
- Suitable in areas with heavy foot and wheeled traffic.
- Over underfloor heating systems.

### Product guidance - As Standard

#### General:

- Colour: Light cream.
- Application temperature: +15–35°C.

### Product specification

#### Manufacturer

- Name: Mapei (UK) Ltd
- Web: [www.mapei.co.uk](http://www.mapei.co.uk)
- Email: [sales@mapei.co.uk](mailto:sales@mapei.co.uk)
- Tel: +44 (0)121 508 6970
- Fax: +44 (0)121 508 6960
- Address: Mapei House, Steel Park Road, Halesowen, West Midlands B62 8HD

**Product reference** Ultrabond Eco Fix

**Mapei (UK) Ltd**  
Mapei House  
Steel Park Road  
Halesowen  
West Midlands  
B62 8HD

Tel: +44 (0)121 508 6970

[www.mapei.co.uk](http://www.mapei.co.uk)  
[sales@mapei.co.uk](mailto:sales@mapei.co.uk)



**rib**productselector.com

A building products library for construction industry professionals

**NBS Plus**