



Ultrabond P913 2K

Generated on 04.04.2020



Detailed description

Used for bonding lamparquet, small and large sized planks and all types of wood on: cementitious screeds; Maprecem, Mapecem Pronto, Topcem, Topcem Pronto screeds and similar, existing flooring in wood, ceramic tiles, marble, terrazzo tiles and anhydrite screeds.

Component A is an epoxy-polyurethane polymer and component B is a hardener in paste form. Mixing the two components results in a uniform coloured product which can be easily applied with a notched trowel and has excellent ridge stability.

After hardening (24 hours at room temperature) by chemical reaction, the product becomes a strong film with high bonding strength to all types of substrates, including those which are non-porous (ceramic). If the substrate is not dry or the residual moisture is above that provided, it is recommended to use a suitable waterproofing primer such as Primer MF, Eco Prim PU 1K, Triblock P etc.

Product guidance - As Standard

Consistency:

Paste.

Application temperature range:

10–30°C.

Set to light foot traffic:

24 hours (approximately).

Product specification

Manufacturer

- Name: Mapei (UK) Ltd
- Web: www.mapei.co.uk
- Email: sales@mapei.co.uk
- Tel: +44 (0)121 508 6970
- Fax: +44 (0)121 508 6960
- Address: Mapei House, Steel Park Road, Halesowen, West Midlands B62 8HD

Product reference Ultrabond P913 2K

Mapei (UK) Ltd
Mapei House
Steel Park Road
Halesowen
West Midlands
B62 8HD

Tel: +44 (0)121 508 6970

www.mapei.co.uk
sales@mapei.co.uk



ribaproductselector.com

A building products library for construction industry professionals

NBS Plus